

Macho Máquina HSS PH-SP

Categorias

- Standard

Aplicação

Macho Máquina até 38 Hrc



Ref.	Descrição	D1	D2	3	4	5	6	7	8	9	10	Passo	Z	DIN
AB140SD4.0IAEEX	M4×0.7-D371-ISO2	M4×0.7	ISO2	3P	63	7	13	21	38	4.5	3.4	6	3	371
AB140SD5.0KAEEX	M5×0.8-D371-ISO2	M5×0.8	ISO2	3P	70	9	14	25	39	6	4.9	8	3	371
AB140SD6.0MAEEX	M6×1-D371-ISO2	M6×1	ISO2	3P	80	11	15	30	45	6	4.9	8	3	371
AB140SD8.0NAEEX	M8×1.25-D371-ISO2	M8×1.25	ISO2	3P	90	-	12	35	47	8	6.2	9	3	371
AB140SD0100AEEX	M10×1.5-D371-ISO2	M10×1.5	ISO2	3P	100	-	13	39	52	10	8	11	3	371
AB140SG012PAEEX	M12×1.75-D376-ISO2	M12×1.75	ISO2	3P	110	-	15	-	56	9	7	10	4	376
AB140SG016QAEEX	M16×2-D376-ISO2	M16×2	ISO2	3P	110	-	18	-	56	12	9	12	4	376
AB140SG020RAEEX	M20×2.5-D376-ISO2	M20×2.5	ISO2	3P	140	-	20	-	71	16	12	15	4	376
AB140SG024SAEEX	M24×3-D376-ISO2	M24×3	ISO2	3P	160	-	25	-	82	18	14.5	17	5	376
AB140SG030TAEEX	M30×3.5-D376-ISO2	M30×3.5	ISO2	3P	180	-	30	-	92	22	18	21	5	376